

CEILING

EdgeMax Loudspeakers

EdgeMax loudspeakers feature proprietary Bose PhaseGuide technology with high-frequency compression drivers to create a new category that combines the room-filling coverage patterns typical of larger surface-mount speakers with the architect-preferred aesthetics of in-ceiling models. Designed to mount near wall-ceiling boundaries, EdgeMax also reduce the number of required units compared to conventional dome-tweeter ceiling speakers.

PhaseGuide technology — provides unique asymmetrical vertical pattern for room-filling coverage when mounting near wall-ceiling boundary

Provides improved visual appearance for rooms with demanding interior designs by eliminating center-of-ceiling or wall-mounted loudspeakers; UL1480A listing for air-handling (plenum) space installation

High-frequency compression driver — for best-in-class audio quality with superior frequency response and coverage consistency versus typical dome tweeters

Nominal 90° (EM90) or 180° (EM180) horizontal coverage — designed for in-ceiling mounting near room edges; 8-inch woofer, 2-way passive crossover with 70/100V transformer

APPLICATIONS

Retail stores

Restaurants and bars

Concourse

Transportation facilities

Resorts and hospitality venues

Houses of worship

Conference rooms



EdgeMax EM90

| Frequency Response (-3 dB) | 50 Hz - 18 kHz |
|--|---|
| Frequency Range (-10 dB) | 45 Hz - 20 kHz |
| Coverage | 90° × 75° (referenced to wall) |
| Nominal Impedance | 8 Ω |
| Power Handling, Continuous | 150 W |
| Power Handling, Peak | 600 W |
| Max SPL @ 1 m | 118 dB |
| Dimensions (across square face × total D × ceiling D) | 390 × 249 × 236 mm 15.4 × 9.8 × 9.3 in |
| Included Accessories | Tile bridge, hole template |
| Optional Accessories | Rough-in pan, black grille, ceiling tile |



EdgeMax EM180

| Frequency Response (-3 dB) | 50 Hz - 18 kHz |
|---|---|
| Frequency Range (-10 dB) | 45 Hz - 20 kHz |
| Coverage | 180° × 75° (referenced to wall) |
| Nominal Impedance | 8 Ω |
| Power Handling, Continuous | 150 W |
| Power Handling, Peak | 600 W |
| Max SPL @ 1 m | 115 dB |
| Dimensions (across square face \times total D \times ceiling D) | 390 × 249 × 236 mm 15.4 × 9.8 × 9.3 in |
| Included Accessories | Tile bridge, hole template |
| Optional Accessories | Rough-in pan, black grille, ceiling tile |

PRO.BOSE.COM

PRO.BOSE.COM