S E R I E S

AVOCOR H SERIES DATASHEET

65" | 75" | 86"

OVERVIEW

The Avocor H Series has a premium feel that will enhance any meeting room, and the technology needed to accommodate high collaboration in hybrid workspaces.

Ensure every in-person and remote interaction provides a natural and intuitive meeting experience with the Avocor H Series, the perfect solution for organizations that demand both a luxury aesthetic and a high performing functional workspace.

In the hybrid work era, the H Series excels in corporate settings with its sleek design and advanced touch technology, enhancing collaboration among remote and in-office teams. Its easy installation and FUSE-powered remote management streamline IT operations, while diverse connectivity options ensure seamless device integration. The addition of Montage and Rise Vision transforms idle screens into dynamic communication hubs, keeping all team members engaged and informed, thus embodying a versatile solution for modern corporate challenges.

<complex-block>

SOLUTION Highlights

Ultra-thin bezel with edge-to-edge glass for a sleek design and 40 points of touch with PCAP technology.



Flexible mounting options and diverse connectivity including a 100W Type C port, for a smooth integration with any technological ecosystem.



Designed to meet the demand of modern workspaces, with quick and easy installation and plug-in-andplay setup.



Monitor and manage your displays from anywhere with FUSE, offering cloud-based efficiency for AV/IT teams.

DisplayNote Montage



Featuring Montage for seamless wireless sharing and Rise Vision for dynamic digital signage, transforms idle displays into hubs of interactive team collaboration



Size	AVH-6520	AVH-7520	AVH-8620
	65	75	86
Backlight		Direct-lit LED	
Aspect Ratio		16:9	
Resolution		3840 x 2160 @ 60Hz	
Response Time	6.5/6.5/8 ms		
Brightness	400 (cd/m2) w/bonded glass		
Contrast Ratio	5000:1		
Viewing Angle	178° / 178°		
Supported Colors	10 Bit 1.07 Billion Color		
Display Orientation		Landscape	
TOUCH SYSTEM			
Interface	2 x USB-B 2.0, 1 x Type C		
Touch	Up to 40 points Touch + 1 stylus		
Glass	Zero parallax, 2mm optically bonded, anti-glare, anti-fingerprint		
Supported Operating Systems	Windows 8+, Mac OSX**, Linux**		
CONNECTIVITY			
Front Inputs/Guest Inputs		None	
Top Inputs	1 x USB-A 3.0 hub		
Bottom Inputs	None		
Side IQ	1 x Type-C (100W PD w/o OPS), 4 x HDMI 2.0, 3 x USB-B 2.0, 1 x DisplayPort 1.4, 2 x USB-A 3.0 hub,		
	1 x USB-A service port, HDMI 2.0 out		
Audio	1 x 3.5mm audio out, 1 x optical (SPDIF)		
Control	1 x RS-232, 2 x LAN Ethernet (RJ-45)		
Ops Slot	Yes		
WiFi		Yes	
AUDIO			
Built-in Speakers	2	x 16W - spatial-stereo downward faci	ng
Microphone Array	None		
Camera	None		
DISPLAY & REMOTE FUNCTIONS			
Auto-Source-Detection		Yes	
Source Preview	UiQ		
Image Settings	UiQ, FUSE		
PHYSICAL SPECIFICATIONS			
	1493 x 80 x 877mm	1714 x 80 x 1002mm	1962 x 80 x 1141mm
Product Dimensions (L x W x H)	58.78" x 3.15" x 35.53"	67.48" x 3.15" x 39.45"	77.24" x 3.15" x 44.92"
Bezel Dimensions		3mm all sides	
Shipping Dimensions (L x W x H)	1612×220×1034mm	1863×225×1130mm	2110×225×1270mm
	63.46" x 8.66" x 40.71"	73.35" x 8.86" x 44.49"	83.07" x 8.86" x 50"
Weight	Net: 37 kgs 81.6 lbs	Net: 48 kgs 105.8 lbs	Net: 61 kgs 134.5 lbs
-	Gross: 49 kgs 108 lbs	Gross: 69 kgs 152 lbs	Gross: 81kgs 178.6 lbs
Wall Mount (VESA)	400 x 400 mm included 600 x 400 mm included		
IPC Mount	100 x 100 mm + 80 x 80mm		
Handles		2	
SENSORS			
Туре		Presence, ambient light	
Presence Sensor	Yes, max 4 range		
POWER		res, max + range	
Max Power Consumption	227W	257W	390W
	22/ VV	23799	57044
ENVIRONMENTAL			
Operating Temperature	0°C ~ 40°C		
Storage Temperature	-20°C ~ 60°C		
Humidity		20% ~ 85%	
WHAT COMES IN THE BOX			
	1 x Remote control & batteries, 2 x soft-tip passive styluses, Wall Mount, AC power cords (1 x UK, 1 x EU, 1 x US, 1 x AUS),1 x USB-B 3.0 cable (3m 118.1 in), 1 x Type-C cable (1.8m 70.9 in), 1 x HDMI cable (3m 118.1 in), 1 x quick start guide		
	Terms and conditions vary via region, please click here		

Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE. **Please note up to 40 point touch in PC mode with Windows 8/10. Mac OSX and Linux only supports single touch. Version date: 01/17/2024