



4K **HDR**


READY FOR ANYTHING

Impressive usability and imaging power combine in the EOS C300 Mark III camera, the customizable cinema camera that's built for versatility and flexibility. The lightweight body comes equipped with Canon's new Super 35mm Dual Gain Output (DGO) sensor, capable of over 16 stops of dynamic range. The DIGIC DV 7 image processor expands functionality and flexibility by enabling features such as internal Cinema RAW Light recording, 4K 120p High Frame Rate recording and Dual Pixel CMOS Autofocus. The EOS C300 Mark III is the perfect expression of form and function, adaptable to virtually any production with its modular design. Three expansion units and user changeable lens mounts enable operators to build their ideal system for cinema or broadcasting.

- Canon Super 35mm Dual Gain Output (DGO) Sensor
- DIGIC DV 7 Image Processor
- Modular Design with Three Available Expansion Units
- Canon Log 2 and 3 Gamma Support
- LM-V2 4.3" LCD Touch Screen Monitor
- 4-channel Audio Recording
- Support for Custom User LUTs
- User Interchangeable Lens Mounts
- Anamorphic Lens Support
- Canon Cinema RAW Light and XF-AVC Recording
- Five-axis Electronic Image Stabilization
- 12G-SDI
- Dual Pixel CMOS AF with Touch AF and Face Detection

Canon Super 35mm Dual Gain Output (DGO) Sensor

This new sensor is capable of dynamic ranges in excess of 16 stops and is compatible with Canon's exclusive Dual Pixel CMOS Autofocus technology. The DGO Sensor is a newly developed imaging system that generates high dynamic range and maintains low noise levels by reading out each pixel with different gains. It combines images using pixels shot with a saturation-prioritizing amplifier for bright areas and a lower-noise noise-prioritizing amplifier for darker areas.



Modular and Customizable

An outstanding modular design with three available expansion units and easy interchangeability between EF, Locking EF (EF-C) and PL mounts allows the EOS C300 Mark III camera to be used in a variety of configurations for a broad range of applications. Users can choose the right look and lens for the project without a costly and inconvenient mount swap.



SPECIFICATIONS

Image Sensing Device	White Balance
Sensor: Super 35mm / Super 16mm (Crop) Sensor with DAF Technology	Kelvin setting (setting range: 2000K to 15000K / -20CC to +20CC), AWB, Daylight, Tungsten, Set A, Set B
Total Pixels: 9.6 Megapixels (4206 x 2280)	System Frequency Selection
Number of Effective Pixels: 8.85 Megapixels (4096 x 2160); 4K/2K DCI Recording 8.29 Megapixels (38040 x 2160); UHD/FHD Recording	Frame Rates: 59.94/59.94P/29.97P/23.98P, 50.00 Hz mode: 50.00i/50.00P/25.00P, 24.00 Hz mode: 24.00P
Image Processing Platform	Recording Media
Image Processor: DIGIC DV 7 Image Processor	CFexpress™ Card: CFexpress™: Recording of movie (Cinema RAW Light/ XF-AVC), custom pictures, metadata (2 slots)
Lens Mount	SD Card: Recording of movie (XF-AVC (proxy)), photos (JPEG), custom pictures, clip metadata, menu settings, SD/SDHC/SDXC Supported
EF-mount (default), EF-mount (cinema lock type) (optional), PL-mount (optional)	Compression Formats
Exposure	Video: (1) XF-AVC: MPEG-4 AVC/H.264, (2) RAW: Cinema RAW Light
Exposure Modes: (1) Manual exposure based on shutter setting, iris setting, ISO/gain setting and ND filter setting (2) Push auto iris control, auto iris control (Light metering system selection, shift possible)	Audio: Linear PCM (24 bit - 48kHz, 4-channel recording)
Shutter Setting: Speed, Angle, Clear Scan, Slow or Off mode selected Either 1/3 or 1/4 steps selected as speed increment	Time Code
Iris Setting: Can be set to 1/2-stop, 1/3-stop or Fine (1) Push auto iris control (2) Auto iris control Lenses that support Auto Iris:	Count Up: (1) Drop frame*, (2) Non-drop frame * Only in 59.94 Hz mode
EF Lenses*	Operation Mode: Regeneration, Record Run, Free Run, External Source
EF-S 10-18mm f/4.5-5.6 IS STM EF-S 55-250mm f/4-5.6 IS STM EF-S 18-55mm f/4-5.6 IS STM EF 85mm f/1.4L IS USM EF-S 18-55mm f/3.5-5.6 IS STM EF 24-105mm f/3.5-5.6 IS STM EF 70-300mm f/4-5.6 IS II USM EF-S 18-135mm f/3.5-5.6 IS STM EF-S 18-135mm f/3.5-5.6 IS USM EF-S 35mm f/2.8 Macro IS STM	Gamma/Color Space
* Supported by EF lenses released in 2018 and later	Gamma: BT.709, Wide DR, Canon Log 2, Canon Log 3, PQ, HLG
CINE-SERVO Lenses	Color Space: Cinema Gamut, BT.709, BT.2020
CN7x17 KAS S/EI CN10x25 IAS S/EI CN20x50 IAS H/EI CN-E 18-80mm T4.4L IS KAS S CN7x17 KAS S/PI CN10x50 IAS S/PI CN20x50 IAS H/PI CN-E 70-200mm T4.4L IS KAS S	Other Features
ENG Broadcast Lenses*	Slow & Fast motion recording, pre-recording, relay recording*, double-slot recording**, custom picture settings, color bar, peaking, zebra pattern, magnify, black and white mode, waveform monitor display, assignable buttons, marker display, custom picture display, control via Browser Remote, peripheral illumination correction * Not available during Slow Motion recording ** Not available in combination with Slow and fast motion recording or relay recording
HJ14ex4.3B IASE S HJ17ex7.6B IASE S CJ45ex13.6B IASE-V H CJ18ex7.6B IASE S HJ18ex7.6B IASE S HJ22ex7.6B IASE S CJ24ex7.5B IASE S HJ24ex7.5B IASE S CJ45ex9.7B IASE-V H CJ14ex4.3B IASE S	Terminals
* 2/3" mount lenses which allow for 12-pin communication using B4 Mount (MO-4E or MO-4P B4 Adapter and Expansion Unit EU-V2 required)	Input: GENLOCK terminal supported with optional Expansion Unit EU-V1 or EU-V2 attached (also serves as SYNC OUT terminal), TIME CODE terminal (input output switching), REMOTE terminal, MIC terminal, AUDIO terminal
ISO: 1 step, 1/3 step settings: 100* - 160 - 25600 - 102400* * When the sensitivity is expanded	Output: MON terminal, REC OUT terminal, HDMI OUT terminal, headphone jack, SYNC OUT terminal supported with optional Expansion Unit EU-V1 or EU-V2 attached (also serves as GENLOCK terminal), TIME CODE terminal (input output switching), VIDEO terminal
ND Filter: 5 density settings (2, 4, 6, 8*, 10* stops) * When expansion is selected, motorized drive	Input/Output Control: System extension terminal (WFT/other unit)
Focus Control/Assist	Power
Focus Control: Dual Pixel CMOS AF (DAF), Manual Focus, One-Shot AF, Continuous AF, AF-Boosted MF, Face Detection AF (Only lenses that support AF functions can be used in these modes)	Supply: 14.4V DC (Battery Pack)
Focus Guide: Available; displays focus status or unfocused status using the AF signal.	Power Terminal: (1) DC IN 12V jack (DC 11.5V-20V) (2) DC 12-20V * When using a V-mount battery with the EU-V2 Expansion Unit
LCD Monitor	Dimensions (W x H x D)
LM-V2 LCD Monitor (Included), 4.3-inch LCD with 16:9 4.0-inch wide-screen LCD with 16:9 aspect ratio, Approx. 2.76 million dots	Approx. 6.0 x 5.8 x 6.6 in. (153 x 148 x 168mm) body only
Viewfinder	Weight
Optional OLED Electronic Viewfinder EVF-V50 or EVF-V70 (sold separately)	Approx. 3.9 lb. (1750g) body only

EOS C300 Mark III System

<p>Included Accessories</p> <ul style="list-style-type: none"> 1 Camera Grip GR-V1 2 Thumb Rest 3 Mic Holder Unit 4 LCD Attachment LA-V2 5 LCD Monitor LM-V2 6 Handle Unit 7 Battery Charger CG-A20 8 BP-A60 Battery Pack 	<p>Optional Accessories</p> <ul style="list-style-type: none"> 9 Mount Kit CM-V1 10 Mount Kit PM-V1 11 B4 Mount Adapter MO-4E/MO-4P 12 Clamp Base CL-V2 13 OLED Electronic Viewfinder EVF-V70 14 OLED Electronic Viewfinder EVF-V50 15 Expansion Unit 1 EU-V1 16 Expansion Unit 2 EU-V2 17 Remote Controller RC-V100 18 GPS Receiver GP-E2 19 Shoulder Support Unit SU-15 20 Shoulder Style Grip Unit SG-I
--	---

Canon
SEE IMPOSSIBLE

CINEMA EOS
cinemaeos.usa.canon.com

Professional **SERVICE & SUPPORT**
Speed. Quality. Excellence.

pro.usa.canon.com/support
855-CINE-EOS

For more info:
pro.usa.canon.com
@CanonUSApro
@CanonUSAprovideo
@CanonUSA
@CanonUSA

Certain images and effects are simulated. Specifications and availability subject to change without notice. Products not shown to scale. Weight and dimensions are approximate. Product shown with optional accessories. Not responsible for typographical errors.
 © 2020 Canon U.S.A., Inc. All rights reserved. Canon and EOS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon is an authorized licensee of the CFast™ trademark, which may be registered in various jurisdictions. All other product names, brand names and logos are trademarks or service marks of their respective owners. Canon makes no representations or warranties with respect to any third party accessory or product mentioned herein. Use of genuine Canon accessories is recommended; these products are designed to perform optimally when used with genuine Canon accessories.

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747 U.S.A.

Canon Burbank
3400 West Olive Avenue
Suite 250
Burbank, CA 91505 U.S.A.

4/20 PRINTED IN THE U.S.A.